



FurnitureLeisure.com PoolFurnitureSupply.com
PicnicFurniture.com PicnicTableSupplier.com
UBrace.com

1-800-213-2401 | sales@furniturelsiesure.com



Model # T46OCTROLLPEDS

3/5/2019 Page 1 of 10



3/5/2019 Page 2 of 10

PRODUCT SPECIFICATIONS

T46OCTROLLPEDS 46" SQUARE INGROUND TABLE WITH 4 SEATS

Top & Seats: Table top frame is 11 gauge die formed angle frame 1"x1-7/8" with 3" radius corners. 3/4" #9 steel expanded metal. 7 gauge x 1-1/2" flat bar center support and mounting bracket understructure. Top is additionally supported to the corners with 7 gauge x 1-1/2" flat bar. Seat end plates are fabricated out of 7 gauge x 3" with a 3" diameter corners. 5/8" rod to finish off expanded edge. Electrically MIG welded.

Coating: Oven fused functionalized polyethylene copolymer-based thermoplastic. Fluidized bed coating application with superior mechanical performance, impact resistance and UV-stability.

Frame: Main support column is 4"x4"x11 gauge pre-galvanized structural steel tubing. Arms are fabricated from 2-7/8" O.D. x 12 gauge pre -galvanized structural steel tubing welded to 1/4" precision punched plates for attachment to the main column and 2"x2"x3/16" structural steel angle for lateral seat support. Seat attachment points are 10 gauge precision punched tabs. Table top attachment structure is fabricated from 2"x2"x3/16" structural steel angle and top attachment points are 7 gauge x 1-1/2" steel flat bar.

Frame Coating: Electrostatic powder coated application oven cured.

Hardware: All stainless steel hardware fasteners.


Dimensions: Top is 46" square x 30-1/4" high. Seats are 12" wide x 36" long x 19" high. Outside to outside dimensions of 4 seat table is 76-1/2" square.

3/5/2019 Page 3 of 10

COMPONENTS 4 **5** PartNo **DESCRIPTION** QTY ITEM NO. T-OV46-T 46" Octagon Expanded Top 1 **VR36-S** 3' Vinyl Rolled Seat 2 4 P-338S or G-338S 3 338 IG post asem 1 H Bracket 4 P-01-04-0150 1 5 P-V338-ARM 338 vinyl arm 4 16 6 33-02-0004 7/16" SS Washer 33-02-0007 5/16" SS Washer 40 33-02-0008 3/8" Flat Washer (SS) 4 9 33-06-0050 7/16" x 5-1/2" Machine Bolt 8 10 20 33-05-0029 5/16" x 1" Machine Bolt (SS) 11 33-01-0006 7/16" Hex Nut (SS) 8 12 33-01-0018 3/8" Hex Nut (SS) 4 20 13 33-03-0012 5/16" Kep Nut (SS) 33-06-0042 3/8" x 1" Carriage Bolt (SS) 4

3/5/2019 Page 4 of 10


STEP 1



Attach the Arms to the Post using specified hardware.

3/5/2019 Page 5 of 10


STEP 2



Attach the H Bracket to the Post using specified hardware.


3/5/2019 Page 6 of 10

STEP 3




Attach the 46" Octagon Top to the H Bracket using specified hardware.


3/5/2019 Page 7 of 10



3/5/2019 Page 8 of 10


FOOTINGS





Estimated Required Concrete: 12 - 50lb Bags of Concrete Mix

3/5/2019 Page 9 of 10



3/5/2019 Page 10 of 10